



## 2026 Volkswagen Golf R Technical Specifications

### Golf R

ENGINE		
Type	2.0L inline four cylinder, 16V, turbocharged/intercooled, TSI (EA888evo4)	
Bore	3.25 in	82.5 mm
Stroke	3.65 in	92.8 mm
Displacement	121 cu in	1984 cc
Compression Ratio	9.3:1	
Maximum Turbo Boost, PSI	21.8	
Horsepower (SAE) @ rpm	328 @ 5850 - 6500	
Maximum Torque, lb-ft @ rpm	295 @ 2000 - 5850	
Fuel Requirement	Premium unleaded recommended	
ENGINE DESIGN		
Arrangement	Front mounted, transverse	
Cylinder Block	Cast iron	
Crankshaft	Forged steel, five main bearings	
Cylinder Head	Aluminum alloy, crossflow	
Valvetrain	Double overhead camshaft, chain driven, four valves per cylinder, maintenance-free hydraulic lifters, variable intake and exhaust timing, variable exhaust-valve lift	
DRIVETRAIN		
Driven wheels	All-wheel drive	
	Automatic (7-Speed DSG)	
Transmission Gear Ratios:1	1st	3.19
	2nd	2.75
	3rd	1.9
	4th	1.04
	5th	0.79
	6th	0.86
	7th	0.66
	Reverse	2.90
	Final I	4.47
	Final II	3.30
CAPACITIES		
Fuel Tank	14.5 gal	55 L
STEERING		
Type	Rack and pinion: electric power assist	
Turns (lock to lock)	1.96	
Turning Circle (curb to curb)	38.1 ft / 11.6 m	
Ratio	10.9:1	
INTERIOR VOLUME - SAE		
EPA Class	Compact cars	
Seating Capacity	5	
Passenger Volume	91.9 cu ft	
Cargo Volume	19.9 cu ft	
Cargo Volume (with rear seats folded)	34.5 cu ft	
	1st row	2nd row
Volume(cu ft)	51.3	40.6
Headroom (in/mm)	38.5/978	38.1/968
Shoulder room (in/mm)	55.9/1420	53.9/1370
Hip room (in/mm)	53.4/1357	46.3/1176
Legroom (in/mm)	41.2/1046	35.0/889



## 2026 Volkswagen Golf R Technical Specifications

### Golf R

BODY, CHASSIS AND SUSPENSION	
Type	Unitary construction, bolt-on front fenders, two solid mounted subframes
Body Material	Steel stampings
Front Suspension	Strut-type with lower control arms, coil springs, telescopic dampers, anti-roll bar
Rear Suspension	Multilink with coil springs, telescopic dampers, anti-roll bar
Brakes	Power assisted, dual circuit, 14.1 x 1.3-in vented front discs and 12.2 x 0.9-in vented rear discs
Stability Control	Standard Electronic Stability Control (ESC)
Parking Brake	Electro-mechanical
Wheels/Tires	19-in x 8J aluminum-alloy wheels 235/35 R19 91Y, summer tires
Drag Coefficient	0.33
DIMENSIONS	
Wheelbase (in/mm)	103.5/2630
Front Track (in/mm)	60.7/1541
Rear Track (in/mm)	59.7/1517
Length (in/mm)	169.1/4296
Width (in/mm)	70.4/1789
Height (in/mm)	57.8/1467
Approach angle (degrees)	13.2
Departure angle (degrees)	20.7
Breakover angle (degrees)	15.1
Ground Clearance (in/mm)	4.8/123
WEIGHTS	
Curb Weight NHTSA (lb/kg)	3461/1570
GVWR (lb/kg)	4542/2060
Payload (lb/kg)	948/430
CONSUMPTION	
City (MPG)	22
Highway (MPG)	31
Combined (MPG)	25

Specifications, equipment, options, and prices are subject to change without notice